



Qingdao XMD Autos Ball Bearing Co., Ltd.

9SRS9WGMC1+[40-1000/1]L[H,P]M THK Miniature Linear Guide Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. 9SRS9WGMC1+[40-1000/1]L[H,P]M

9SRS9WGMC1+[40-1000/1]L[H,P]M Bearing 2D
drawings and 3D CAD models

Days to Ship	3 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	9
Nominal Part Number	9W
Rail Type	Wide Rail
Rail Width W1	18 mm
Mounting Height M	12 mm
Rail Length L	40 ~ 1000 mm
Radial Clearance	Light Preload
Accuracy Grade	High Grade / Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	2670
Basic Load Rating Static Rating Co(N)	3350
Allowable Static Moment MA(N m)	13.9
Allowable Static Moment MB(N m)	16.6
Allowable Static Moment MC(N m)	31.7
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	30 mm
Block external dimension L	39 mm



Qingdao XMD Autos Ball Bearing Co., Ltd.

Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	2.8 mm
Block dimension L1	27 mm