



**9SRS20GM[SS,SSH,UU]C1+[51-900/1]L
M THK Miniature Linear Guide Full Ball SRS-G
Accuracy and Preload Selectable**

Bearing No. 9SRS20GM[SS,SSH,UU]C1+[51-900/1]LM

9SRS20GM[SS,SSH,UU]C1+[51-900/1]LM
Bearing 2D drawings and 3D CAD models

Days to Ship	22 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	9
Nominal Part Number	20
Rail Type	Standard
Rail Width W1	20 mm
Mounting Height M	20 mm
Rail Length L	51 ~ 900 mm
Radial Clearance	Light Preload
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	5950
Basic Load Rating Static Rating Co(N)	9400
Allowable Static Moment MA(N m)	44.7
Allowable Static Moment MB(N m)	53.3
Allowable Static Moment MC(N m)	91.4
Symbols for Dust Resistance	UU: End Seals
Advanced Seal Options (Longer Leadtime)	SSH: SS + Laminated Contact Scraper LaCS



Qingdao XMD Autos Ball Bearing Co., Ltd.

Block external dimension W	40 mm
Block external dimension L	32 mm
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M4
Mounting Hole Screw Depth	6 mm
Block dimension L1	34 mm